

CLAIMS

1. A transducer-supporting structure, characterized in that said structure at least comprises:

a transducer for recording and reproducing information on and from a medium;

a transducer mounting section which is mounted with said transducer and comes into contact with said medium by means of mechanical action or keeps a fixed distance from said medium;

a suspension which supports said transducer mounting section and elastically positions said transducer in the direction such as to bring and separate said transducer close to and from said medium; and

a thermal coupling member for thermally coupling said transducer with said suspension, and

heat generated in said transducer is dissipated through said suspension.

2. The transducer-supporting structure according to claim 1, characterized in that said thermal coupling member has an elastic restoring force, and is in contact with said transducer.

3. The transducer-supporting structure according to claim 1, characterized in that said thermal coupling member is formed of a part of said suspension.

4. The transducer-supporting structure according to claim 1, characterized in that said thermal coupling member and said transducer or said thermal coupling member and said suspension are partially coupled thermally with each other via a viscous fluid.

5. The transducer-supporting structure according to claim 1, characterized in that said thermal coupling member is a gel-form substance, and said transducer and said suspension are coupled thermally with each other via said gel-form substance.

6. The transducer-supporting structure according to claim 1, characterized in that said transducer is an electromagnetic transducer.

7. The transducer-supporting structure according to claim 1, characterized in that said transducer is an electro-optical transducer.

8. A transducer-supporting structure,  
characterized by at least comprising:

a transducer for recording and reproducing  
information on and from a medium;

heat dissipating means mounted on said transducer;  
and

a suspension for holding said transducer at a desired  
position with respect to said recording medium.

9. The transducer-supporting structure according to claim 8, characterized in that said heat dissipating means is formed integrally with said transducer.

10. The transducer-supporting structure according to claim 8, characterized in that said transducer is an electromagnetic transducer.

11. The transducer-supporting structure according to claim 8, characterized in that said transducer is an electro-optical transducer.

12. A transducer-supporting structure, characterized in that said structure at least comprises:

a transducer for recording and reproducing information on and from a medium;

a transducer mounting section which is mounted with said transducer and comes into contact with said medium by means of mechanical action or keeps a fixed distance from said medium; and

a suspension which is in direct contact with said transducer, supports said transducer mounting section, and elastically positions said transducer in the direction such as to bring and separate said transducer close to and from said medium, and

heat generated in said transducer is dissipated through said suspension.

13. The transducer-supporting structure according to claim 12, characterized in that heat generated in said transducer is transmitted to said suspension through said directly contacting portion, and is dissipated.